



PRE-MIXED CONCRETE REPAIR

DESCRIPTION AND USES

Concrete Saver Pro Pre-Mixed Concrete Repair is a ready to use material for the repair of holes, cracks, and other imperfections in concrete or masonry surfaces. The product is excellent for tuck pointing masonry and brick work. It may also be used as a “glue” to join broken pieces of concrete or brick. **DO NOT USE AS A SKIM COAT.** The material dries to a concrete-gray color.

PERFORMANCE CHARACTERISTICS

- Ready mixed, easy to use
- Repairs cracks and breaks in concrete and masonry
- Durable and non-shrinking
- Can be used to spot level
- Ideal for filling holes, cracks, dents, and defects on concrete.

PRODUCT

SKU	DESCRIPTION
392528	1 Gallon

PRODUCT APPLICATION

SURFACE PREPARATION

Use a wire brush, chisel, or similar tool to remove all loose material, dust, dirt, oil, and grease from the area to be repaired. Use a solvent to remove oil and grease. Rough up the surface one or two inches beyond the area to be repaired for a good bond. Dampen the area with clean water – **DO NOT FLOOD.**

PRODUCT APPLICATION (cont.)

MIXING

Stir the patch to a smooth consistency; no thinning is required.

APPLICATION

Apply only when air, material, and surface temperatures are between 40-90°F (4-32°C) and the relative humidity is below 85%. Apply with a putty knife, broad knife, trowel, or other suitable tool, Work the material well into distressed areas, filling flush and feathering edges. If area to be patched is deeper than 1/2 inch, apply patch in 1/4-inch layers, maximum depth 1 inch, allowing each application to dry. If used as a “glue,” apply at least one layer of concrete patch to both surfaces to be repaired. Push the pieces together and use bracing or weights to support the assembly during cure. Patched areas may be painted with a quality latex paint after 2 to 4 hours or alkyd paint after 24 hours if desired.

DRY TIME

Allow to dry 24 hours before driving over patched area. Do not apply if rain is likely within drying period or if temperature is apt to drop below 40°F.

CLEAN-UP

Clean hands and tools with soap and water. Dry material must be chiseled or scraped away.

STORAGE

Keep from freezing. Close container tightly after each use.



PRE-MIXED CONCRETE REPAIR

PHYSICAL PROPERTIES

		PRE-MIXED CONCRETE REPAIR
Composition		Latex Emulsion
Weight	Per Gallon	25.05 lbs.
Solids	By Weight	83%
pH		7-12
Volatile Organic Compounds		13 g/l
Shelf Life		1 years
Practical Coverage		Will depend on the method of application and surface type
Flash Point		>200°F (93°C)
Safety Information		For additional information, see SDS

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.