

• TRUSTED QUALITY SINCE 1921 •



**RUST-OLEUM®
ROOF PATCH CLEANER & PRIMER**

DESCRIPTION AND USES

Rust-Oleum® Roof Patch Cleaner & Primer is a solvent-based cleaner that clears away dirt and debris and contains an adhesion promoter to increase adhesion of roof patch and sealant products to existing roof substrates. When used with the Rust-Oleum Triple Thick Roof Patch & Sealer the quick-dry formulation is ideal for efficient roof repairs saving both time, and money while providing long-term protection from leaks.

Use on a variety of roofing substrates including metal, aluminum, Kynar®, concrete, modified bitumen, gutters, all single-ply membranes, and previously coated substrates not including silicone coatings. (Kynar® is a trademark of Arkema, Inc.)

PRODUCT

SKU	DESCRIPTION (Clear - 13 oz. Aerosol)
345815	Roof Patch Cleaner & Primer

COMPANION PRODUCTS

SKU	DESCRIPTION (13 oz. Aerosol)
345813	Triple Thick Patch & Sealer Black
345814	Triple Thick Patch & Sealer White
346240	Triple Thick Patch & Sealer Clear

SKU	ROOF PATCH FABRIC
301948	Polyester Patching Fabric 4"x50'
345650	Self-Adhering Roof Fabric 4"x16'
345651	Self-Adhering Roof Fabric 4"x25'

NOTE: Do not use on asphalt-based, granule, and porous substrates.

PRODUCT APPLICATION

APPLICATION

Use outdoors or in a well ventilated area. Use when temperature is between 40-120°F (10-48°C) and humidity is below 85% to ensure proper drying.

Shake can vigorously for one minute after mixing ball begins to rattle. Shake often during use. If mixing ball fails to rattle DO NOT STRIKE CAN. Contact Rust-Oleum. Apply product directly to substrate and lightly saturate the surface. After 15-30 seconds, wipe clean using a rag or cloth, and immediately apply roof patch and repair product directly to the cleaned surface.

TOPCOAT: Immediately after wiping.

CLEAN-UP

Wipe tip off before storing. Clean up wet or dry coating with Xylene or mineral spirits. Throw away empty can in trash pick-up. Do not burn or place in home trash compactor.

PHYSICAL PROPERTIES

ROOF PATCH CLEANER & PRIMER	
Pigment Type	Titanium Dioxide, Zinc Oxide
Weight Per Gallon	6.6 lbs.
Volatile Organic Compounds	642 g/l
Shelf Life	5 years
Safety Information	For additional information, see SDS

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.